

TL PART NO.	INDUSTRY NUMBER	RATED VOLTAGE	CURRENT	BEAM CANDLE POWER (approx)	LAB. LIFE est. hrs. at rated voltage	PRODUCT
420336	1156	12.8	2.1	5,000	1200	MV2IND-12
420619	n/a	24.0	0.625	4,000	2000 ^(a)	MV2IND-24
420620	n/a	36.0	0.828	4,000	200 ^(b)	MV2IND-36
420630	n/a	48.0	0.41	3,000	2000 ^(c)	MV2IND-48
420334	1195	12.5	3.0	7,000	300	MVMAG, MR3
426000	795	12.8	3.9	10,000	200	SW1, MR3H
420420	4416-1	12.8	2.34	35,000	300	RF6-12, RF110, SW2
420705	25T8DC	120	0.22	4,000	200	MV110, SG110
420416	4435	12.8	2.34	75,000	100	MARK12
420715	100A/CL	12.8120	0.83	8,000	750	MARK6
420336	1156	12.8	1.1*	N/A	1200 ^(d)	SG12
423033	#1665	28.0	0.4*	N/A	1000 ^(d)	SG24
426006	H-7600	12.8	2.92	60,000	300	TB-8

- (a) estimated life for 32 v. rated lamp operated at 24 v.
- (b) estimated life for 40 v. rated lamp operated at 36 v.
- (c) estimated life for 64 v. rated lamp operated at 48 v.
- (d) estimated life may be derated due to flashing condition
- * average current draw for flashing operation