

# **Alarms - Audible**

# **Electronic Back-Up Alarms**

### LTA-2 - Two Sound Levels

- Multi-voltage for 12 to 48 volts DC operation
- Two sound levels: 97dB or 87 dB measured at 3 feet
- Draws less than 0.2 amps at 48 volts
- · Suitable for indoor and outdoor use
- · Resistant to moisture
- · Aids in compliance with safety regulations
- · Simple to install

## FEA-1 – Economically Priced

- All solid-state circuitry
- For 12 volt DC applications
- Sound level = 97dB at 3 feet
- Draws less than 0.6 amps at 12 volts DC
- Operates at extreme temperature ranges
- · Water resistant
- · Easy installation



5 1/8" high, 33/4" wide, 21/8" deep. Shipping weight - 1 lb.

# CVA – 8" Diameter Mechanical Alarm Big sound output at a low price!

- Rugged wheel-mounted 8" bell, mounts easily with standard tools
- As vehicle moves, four gravity actuated hammers ring every 1/4 turn of the wheel
- Completely mechanical; no wires or switches
- Made of zinc plated 10 gauge steel
- Sounds with rearward movement when mounted on right side
- Sounds with forward movement when mounted on left side
- Universal mounting plate adapter (CVAUMP) available for odd bolt patterns

8" diameter, 3" depth. Shipping weight - 6 lb.

# MUCH. CVA Company and an analysis Or an anal

# BKA – 6" Diameter Mechanical Alarm Great for public safety and industrial applications

- Rugged wheel mounted 6" bell, easy to install
- Two internal hammers sound when vehicle moves
- Can be set to sound in either forward or reverse motion on either side of vehicle
- Completely mechanical; no wires or switches
- Made of zinc plated 10 gauge steel

6" diameter bell, 3" depth, 71/4" diameter mounting plate. Shipping weight - 4 lb.



### **Electro-Mechanical Sirens**

# VS1 (DC) and VS110 (AC)

- DC (12V) and AC (115V) models available
- Sound level = 101dB at 10 feet
- Chrome grill and pedestal mount are standard features
- · Ideal for signaling personnel and animals
- Can be operated continuously for up to 60 seconds
- 115 volt model draws 8-10 amps on start and 2-3 amps when operating

61/2" high, 7" long, 51/2" wide. Shipping weight - 33/4 lb.

