



DLCGN Classic Gooseneck Dock Light



Our Classic Gooseneck Dock Light combines powerful illumination with precision control, featuring a high-performance light head mounted on a durable, flexible gooseneck arm. Engineered for versatility, this design allows for effortless positioning and extended reach around dock door tracks—delivering targeted task lighting exactly where it's needed, even in the most demanding environments.

Features

- **Flexible Positioning:** Flexible gooseneck arm allows for precise light placement around dock door tracks.
- **45° Light Head Adapter:** Directs light deeper into trailers with minimal repositioning.
- **Sag Resistant:** Vertical flex-arm orientation minimizes sag, while a steel outer arm with internal spring maintains position through tens of thousands of cycles and increases rigidity with continued use
- **Impact Resistant:** Arm and light head design absorb and deflect impact to protect internal components.
- **Durable:** Sturdy polycarbonate enclosure and light head resists impact, corrosion, and discoloration.
- **Multiple Light Head Options:** Choose from three light head configurations. P and PLED versions include wire guard.
- **Easy Installation:** Key-slot mounting and prewired design for easy installation.
- **Made in the USA:** Engineered and assembled in Chicago.

Ordering Information

Arm Style		Light Head		Arm Length
DLCGN	Classic Gooseneck Dock Light	L2	Integrated LED Module	27
		P	E26 socket, bulb not included	
		PLED	E26 socket, LED bulb included	

Example: DLCGN-L2-27

Arm Style	Light Head	Arm Length
-----------	------------	------------





DLCGN

Classic Gooseneck Dock Light

Specifications			
Configuration	L2	PLED	P
Wattage	16.3 W	15 W	*
Electrical	120V. 50/60 Hz		
Lumens	1669	1010	*
Beam Angle	10°	15°	*
CRI	80	75	*
CCT	5000K	6000K	*
Housing Material	Polycarbonate head & housing, steel neck		
Weight	9 lbs	8.8 lbs	*
Neck Length	27 In.		
Cord Length	6 ft.		
Plug Type	NEMA 5-15P		
Environmental Rating	Damp Location		
Compliances	UL/cUL Listed. RoHS compliant.		
Warranty	3 years		

NOTES

Values marked with * indicate specifications will vary depending on customer-supplied PAR38 bulb.

P and PLED versions include wire guard (not pictured).

