



DL2 Loading Dock Arms & LED Light Heads

Innovative. Modern. Streamlined.

Model Numbers

24" Loading Dock Arm

DL2-SA-24

36" Loading Dock Arm DL2-SA-36

40" Loading Dock Arm DL2-DA-40

48" Loading Dock Arm DL2-DA-48

60" Loading Dock Arm DL2-DA-60









Heavy Duty LED Light Head

HDL2 (no switch) HDL2-S (switch)

Polycarbonate LED Light Head

PL2 (no switch) PL2-S (switch)

3-Speed Fan DLFAN







Specifications

Wattage	13.4W		
Power Source	120V, 60Hz		
Lumens	1331		
Beam Angle	10°		
CRI	≥ 75		
ССТ	5000K		
Life	100,000 hours at 70% lumen maintenance		
Material	Cast aluminum (HDL2, HDL2-S); Polycarbonate (PL2, PL2-S)		
Compliances	cULus listed, IP66 rated (HDL2), LM79 report available upon request		
Warranty	3 years		

How To Order

The **DL2 Loading Dock Arm** is designed to be used with an **LED Light Head**. If you intend to use a Tri Lite LED Light Head with a loading dock arm other than the DL2 Series, we recommend purchasing the version with a switch. Contact Tri Lite at (800) 322-5250 or (773) 384-7765, or by email at info@triliteinc.com to place an order using the model numbers indicated above.



Made in USA Patented Design









Tri lite

DL2 Loading Dock Arms & LED Light Heads

Innovative. Modern. Streamlined.


Single Arm Lengths









Double Arm Lengths









Model	A	В	C	D	Accessories
DL2-SA-24 (24" Single Arm)	24 in (610 mm)	N/A	8.5 in (216 mm)	8.5 in (216 mm)	HDL2, HDL2-S, PL2, PL2-S, DLFAN
DL2-SA-36 (36" Single Arm)	36 in (915 mm)	N/A	8.5 in (216 mm)	8.5 in (216 mm)	HDL2, HDL2-S, PL2, PL2-S, DLFAN
DL2-DA-40 (40" Double Arm)	40 in (1016 mm)	24 in (610 mm)	8.5 in (216 mm)	8.5 in (216 mm)	HDL2, HDL2-S, PL2, PL2-S, DLFAN
DL2-DA-48 (48" Double Arm)	48 in (1219 mm)	24 in (610 mm)	8.5 in (216 mm)	8.5 in (216 mm)	HDL2, HDL2-S, PL2, PL2-S, DLFAN
DL2-DA-60 (60" Double Arm)	60 in (1524 mm)	36 in (915 mm)	8.5 in (216 mm)	8.5 in (216 mm)	HDL2, HDL2-S, PL2, PL2-S, DLFAN



