



"DL2GN" Sag Resistant Gooseneck

Innovative. Modern. Streamlined.



Unmatched Performance


The DL2GN Gooseneck is designed to resist sag while providing unrivaled flexibility and light quality compared to traditional models.


The DL2GN Gooseneck features "set and forget" positioning, allowing operators to set the model to their optimal position and leave it without obstructing forklifts or the door. Our innovative design resists sag over time by transferring movement to a base hinge, significantly reducing friction caused by repetitive movement and repositioning, and reducing the size and weight of the neck. The model also includes a US-made high-impact polycarbonate head with optimized internal LED, further reducing weight compared to PAR38 lamps and metal heads.

Tri Lite uses the same light engine for the entire DL2 family, ensuring consistent high-quality features like CRI, color temperature, beam angle, and maximum-minimum ratios for all DL2 Series loading dock lights.

Features

- Uses up to 94% less energy than traditional incandescent heads
- 100,000 hour life expectancy in typical applications (vs. 2,000 hours for typical incandescent lights)
- Conveniently stores flat against the wall when not in use
- Safety bumper protects operators from injuries and mitigates damage to the product
- Universal LED engine across all DL2 products
- Fixed wattage, eliminates the danger of incandescent lamps being screwed into LED fixtures.
- 5-year warranty
- UL and cUL Listed
- Made in USA













"DL2GN" Sag Resistant Gooseneck

Innovative. Modern. Streamlined.

Specifications

Specification	ons	
SKU	DL2GN	
Wattage	13.4W	3 1/2"
Power Source	120V, 60Hz	(8.89cm)
Lumens	1331	
Beam Angle	10°	
CRI	≥ 75	
ССТ	5000K	
Life	100,000 hours at 70% lumen maintenance	
Material	Steel, polycarbonate, aluminum	
Mounting	Use 3/8" lag bolts for installation (not included). Recommended bracket mounting height is 4–5 feet (121-152cm) from the floor and 2.5–9 inches (6–22cm) from the edge of the door opening.	
Compliances	cULus listed, LM79 report available upon request	
Warranty	5 years	
Weight	7.46 lbs	19 ¾" (50.165cm)
	15 ¾" (40.005cm) 8 ½" 6 ¾" 3 1¾6" (21.59cm) (17.46cm) (9.525cm)	2" (5.08cm)



